

# Material Safety Data Sheet

---

Issued Date: 06/12/2016

## HOLDENBOND HB577

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Thread Sealant
Product Grade:	HB577
Product type:	Methylic acrylate
Recommended use:	Adhesive / bonding compound
Company name:	USAMERITRADE INC.
Company Address:	5407, Cheyenne Knoll Place, Alexandria VA22312
Telephone:	202-679-8881
Email:	USAmeritrade@gmail.com

### 2. COMPOSITION INFORMATION

Chemical name:	CAS	Proportion (%)
Polyglycol dimethacrylate	25852-47-5	30~60
Vinyl resin	63148-65-2	5 ~10
Alkyl C12 methacrylate	142-90-5	5 ~10
Poly (ethylene)	9002-88-4	1 ~5
Silica, amorphous, fumed, Crystalline-free	112945-52-5	1 ~5
1 -Acetyl-2-phenylhydrazine	114-83-0	0.1 ~1

### 3. HAZARDS IDENTIFICATION

Relevant routes of exposure:	eye, skin, Inhalation, Ingestion
Potential Health effects:	
Inhalation:	May cause respiratory tract, suck steam may cause nose and Breath stimulation, dazed, weakness, tiredness, surfeit, Headache, the serious one may lose consciousness.
Skin contact:	Moderate skin irritation. May cause allergic skin reaction.
Eye contact:	Contact with eyes will cause irritation, stimulation, rubefaction, weep, eyesight faintness.
Ingestion:	May be harmful if swallowed.

# **Material Safety Data Sheet**

---

## **4. FIRST AID MEASURES**

Inhalation:	Remove to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if symptoms occur.
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get medical attention.
Ingestion:	Do not induce vomiting. Keep individual calm. Obtain medical attention.

## **5. FIRE-FIGHTING MEASURES**

Flash point:	≥100°C
Auto ignition temperature:	Not available
Extinguishing media:	If product is involved in fire extinguish with dry chemical, foam or carbon dioxide.
Firefight proceeding:	Wear self-contained breathing apparatus and full protective clothing, cooling the equipment with cold water.
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur, Oxides of nitrogen, Irritating organic vapors.

## **6. ACCIDENTAL RELEASE MEASURES**

Environmental precautions:	Prevent product from entering drains or open waters.
Clean-up methods:	Ventilate area of spill; keep away from kindling; avoid sucking a great deal of steam, absorb with the sand /earth and dispose to chemical waste bin, dispose in accordance with pertinent national legislation.

# **Material Safety Data Sheet**

---

## **7. HANDLING AND STORAGE**

Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Keep light fold and put. Prevent the packing and container from mangling.
Storage:	For safe storage, store at or below 38°C. Keep in a cool, well-ventilated area away from heat, sparks and open flame, avoid sun shine directly, Keep container tightly closed until ready for use. Avoid contacting with strong oxidizers. Strong alkalis. Strong acid, other polymerization initiators.

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Engineering controls:	No specific ventilation requirements noted, but forced ventilation may still be required if concentrations exceed occupational exposure limits.
Respiratory protection:	Usually never need special protection, wear self-breathed filtrated gas mask if there is potential to exceed exposure limit (s).
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves.
Eye/face protection:	Wear safety chemical goggles/glasses chemical.
Body protection:	Wear general safety clothes.
Hand protection:	Wear chemical safety glove.
Ventilation:	Good general or local exhaust ventilation are required for usage

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance and properties:	Dark yellow Paste
Specific gravity:	1.15—1.20
Odor:	Characteristic
Solubility:	Solved in organic solvent. Solved in water slightly.
pH:	3-6
Boiling point:	Not available
Melting point:	Not available
Flash point:	≥100°C

# **Material Safety Data Sheet**

---

## 10. **STABILITY AND REACTIVITY**

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Exposure to sunlight. Heat, flames and sparks.
Incompatibility:	Strong oxidizers. Strong alkalis, strong acid, other polymerization initiators.
Hazardous decomposition:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Phenols.
Products:	Irritating organic vapors.

## 11. **TOXICOLOGICAL INFORMATION**

Estimated oral LD50:	Greater than 10000mg/kg (rat).
Estimated dermal LD50:	Greater than 5000 mg/kg (rabbit).

## 12. **ECOLOGICAL INFORMATION**

Ecological information:	Not available
-------------------------	---------------

## 13. **DISPOSAL CONSIDERATIONS**

Recommended method of disposal:	Dispose of according to local governmental and environment protection department regulations.
---------------------------------	-----------------------------------------------------------------------------------------------

## 14. **TRANSPORT INFORMATION**

Proper transportation name:	Unrestricted
Air transportation name:	Unrestricted
Water transportation name:	Unrestricted

## 15. **REGULATORY INFORMATION**

Product and its compositions are not in toxic goods classify of «chemicals catalog in existence» .

# ***Material Safety Data Sheet***

---

## 16. **OTHER INFORMATION**

Disclaimer: The data contained herein are furnished in the basis of our knowledge and understanding of current country laws and regulations. Without foreordained written notice, the product can't be used in purpose out of the MSDS. It's the user's responsibility to adopt necessary methods in comply with the requirement of the applied rule of laws.