

TECHNICAL DATA SHEET

August 30, 2019

HOLDENBOND® **COPPER ANTI-SEIZE PASTE**

DESCRIPTION:

HOLDENBOND Copper Anti-Seize Paste is a soft copper coloured grease used to prevent seizure caused by metal to metal contact under arduous conditions. The product is both thermally and mechanically stable, very water repellent and will naturally adhere to metal surfaces.

APPLICATIONS:

HOLDENBOND Copper Anti-Seize Paste is recommended for most applications where metal to metal contact needs to be avoided and for all assembly work where ease of dismantling is required, including; keys, keyways, track adjusters, rock drill extension rods, most threaded connections and general assembly work.

HOLDENBOND Copper Anti-Seize Paste is especially recommended for applications where the presence of lead (contained in many other anti-seize compounds) is unacceptable.

BENEFITS:

Very long lasting product.
Lead free.
Easy to apply, naturally adheres to metal and gives maximum coverage.
Mechanically stable.
Very broad temperature range – Non-melting.

TYPICAL PHYSICAL CHARACTERISTICS:

| | |
|-------------------------|-------------------------------|
| Appearance | Smooth Grease. |
| Colour | Gold / Copper. |
| Thickener | Highly refined Modified Clay. |
| Solid Lubricant Content | >20%. |
| Penetration (IP 50) | 280 – 320. |
| Temperature Range | -20°C to + 1100°C. |
| Drop Point | None (Infusible product). |

PACKAGING:

Available in 500g/Tin & 1000g/Tin.

NingBo JunGuan Sealing Technology Co., Ltd
ZheJiang Province, Ningbo City, CiXi City, GuanHaiWei Town,
HuBin Road No.68, Postal 315300.
Email: sales@apexjunguan.com
Tel: 0574-56652686 | Fax: 0574-56652685